



29 APR 2005 533368



(43) International Publication Date
21 May 2004 (21.05.2004)


PCT

(10) International Publication Number
WO 2004/042843 A2

- | | |
|---|---|
| <p>(51) International Patent Classification⁷: H01M</p> <p>(21) International Application Number:
PCT/US2003/034541</p> <p>(22) International Filing Date: 30 October 2003 (30.10.2003)</p> <p>(25) Filing Language: English</p> <p>(26) Publication Language: English</p> <p>(30) Priority Data:
50,422,616 30 October 2002 (30.10.2002) US</p> <p>(71) Applicant (for all designated States except US): NU-
VERA FUEL CELLS, INC. [US/US]; 20 Acorn Park,
Cambridge, MA 02140 (US).</p> <p>(72) Inventors; and</p> <p>(75) Inventors/Applicants (for US only): LEN, Gregory, D.
[US/US]; 152 Pleasant Street, Apt. 1, Arlington, MA</p> | <p>02474 (US). MUELLER, Fortunat, J. [CH/US]; 289
Medford Street, Apt. #1, Somerville, MA 02143 (US).
RIZZO, Vincent [US/US]; 8 Bay State Avenue, Apt. 3,
Somerville, MA 02144 (US).</p> <p>(74) Agents: SMITH, James, M. et al.; Hamilton, Brook,
Smith & Reynolds, P.C., 530 Virginia Road, P.O. Box
9133, Concord, MA 01742-9133 (US).</p> <p>(81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR,
CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD,
GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR,
KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN,
MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU,
SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.</p> <p>(84) Designated States (regional): A IPO patent (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,</p> |
|---|---|

[Continued on next page]

- (54) Title: METHOD AND SYSTEM FOR CONTROLLING FLUID FLOW IN A FUEL PROCESSING SYSTEM



(57) **Abstract:** Fuel processing systems, which reform a hydrocarbon fuel to produce hydrogen suitable for use in a fuel cell, have multiple air inlets for various process steps. Controls and feedback loops are correspondingly complex. Controlling the multiple airflows to a pressurized fuel processor using a single onboard compressor and a number of low pressure drop valves is a significant challenge to overcome in the process of getting a reformer on board a vehicle. A method has been developed for controlling the compressor speed based on the airflow demand of the partial oxidation (POX) zone, without direct feedback from the other airflows in the system. This ensures that the principal zone of air consumption always gets the appropriate amount of air, thus controlling the temperature of that zone and the reaction chemistry effectively. This method also allows removal of extra flow sensors from airflows where the effect of changed airflow (e.g. temperature change) can be used as a feedback to an air controller instead of the actual airflow itself. Similar principles are applicable in the control of other flows, such as fuel and water, when several flows are fed by a common source.

BEST AVAILABLE COPY

WO 2004/042843 A2